

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 September 2003 (12.09.2003)

PCT

(10) International Publication Number
WO 03/074842 A1

(51) International Patent Classification⁷: **F01L 1/18**

[KR/KR]; 369, Galsan 2-dong, Bupyeong-gu, Incheon 403-804 (KR).

(21) International Application Number: PCT/KR03/00426

(22) International Filing Date: 5 March 2003 (05.03.2003)

(74) Agent: NAM, Sang-Sun; 8th Fl., The Korea Chamber of Commerce & Industry Bldg., #45, Namdaemoonno 4-ga, Jung-gu, Seoul 100-743 (KR).

(25) Filing Language: Korean

(81) Designated States (*national*): CA, US.

(26) Publication Language: English

(84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR).

(30) Priority Data:
10-2002-0011540 5 March 2002 (05.03.2002) KR

(71) Applicant (*for all designated States except US*): GM
DAEWOO AUTO & TECHNOLOGY [KR/KR]; 199-1,
Cheongcheon-dong, Bupyeong-gu, Incheon 403-714 (KR).


Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): OH, Jae-Ook

(54) Title: **ROCKER ARM SHAFT FOR AN AUTOMOBILE ENGINE**



(57) Abstract: Disclosed is a rocker arm shaft for an automobile engine, which is effectively capable of offsetting the length change of the rocker arm shaft, which caused by heat. According to an embodiment of the present invention, a rocker arm shaft can be divided into at least two shafts. An elastic member, such as a coil spring, is positioned between the shafts. When the length change of the shafts is changed by heat, the elastic member offsets the changed length of the shafts. The rocker arm shaft is divided into a hollow first shaft and a hollow second shaft. A one end of the second shaft of the rocker arm shaft forms a receiving groove for inserting the elastic member. With this structure, the rocker arm shaft for an automobile engine does not bend nor get twisted by offsetting the changed length of the shafts by means of the elastic member.

WO 03/074842 A1